

according to Regulation (EC) No 1907/2006

2-Propanol (Isopropyl alcohol/IPA), 250 ml

Print date: 15.04.2015 Product code: 9991813 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2-Propanol (Isopropyl alcohol/IPA), 250 ml

CAS No: 67-63-0
Index No: 603-117-00-0
EC No: 200-661-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

1.3. Details of the supplier of the safety data sheet

Seller

Company name: CONATEX-DIDACTIC Lehrmittel GmbH

Street: Im Forstgarten 1
Place: D-66459 Kirkel
Internet: www.conatex.com

Supplier

Company name: Carbolution Chemicals GmbH Street: Im Stadtwald, Gebäude A1.2

Place: D-66123 Saarbrücken

Contact person: Dr. Michael Bauer Telephone: +49 (0)681 302-71232

e-mail: michael.bauer@carbolution-chemicals.de

Internet: www.carbolution-chemicals.de

1.4. Emergency telephone +49 (0)681 302-71232

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: F - Highly flammable, Xi - Irritant

R phrases: Highly flammable. Irritating to eyes.

Vapours may cause drowsiness and dizziness.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Hazardous components which must be listed on the label

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger



according to Regulation (EC) No 1907/2006

2-Propanol (Isopropyl alcohol/IPA), 250 ml

Print date: 15.04.2015 Product code: 9991813 Page 2 of 8

Pictograms:

GHS02-GHS07





Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: C3H8O Molecular weight: 60,1

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	100 %
67-63-0	F - Highly flammable, Xi - Irritant R11-36-67	
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.3. Indication of any immediate medical attention and special treatment needed

No data available



according to Regulation (EC) No 1907/2006

2-Propanol (Isopropyl alcohol/IPA), 250 ml

Print date: 15.04.2015 Product code: 9991813 Page 3 of 8

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water. Carbon dioxide (CO2). Foam. Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition.

- No smoking.

Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

2-Propanol (Isopropyl alcohol/IPA), 250 ml

Print date: 15.04.2015 Product code: 9991813 Page 4 of 8

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Eye protection: Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Hand protection

Hand protection: Single-use gloves. Before using check leak tightness / impermeability. Use gloves only once. German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Skin protection

Body protection: Lab apron. Only wear fitting, comfortable and clean protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protective equipment: particulates filter device (DIN EN 143).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: No data available

Test method

pH-Value: No data available

Changes in the physical state

Initial boiling point and boiling range: 82 °C Sublimation point: No data available Softening point: No data available Flash point: 12 °C

Flammability

Solid: No data available
Gas: No data available
Lower explosion limits: 2 vol. %
Upper explosion limits: 12,7 vol. %
Ignition temperature: No data available

Auto-ignition temperature

Solid: No data available
Gas: No data available

Vapour pressure: 43,2 hPa

(at 20 °C)

Vapour pressure: 58,7 hPa

(at 25 °C)

Density: 0,785 g/cm³
Water solubility: No data available
Partition coefficient: 0,05



according to Regulation (EC) No 1907/2006

2-Propanol (Isopropyl alcohol/IPA), 250	mı
---	----

Print date: 15.04.2015 Product code: 9991813 Page 5 of 8

Viscosity / dynamic:

Viscosity / kinematic:

No data available

Flow time:

No data available

Vapour density:

No data available

Evaporation rate:

No data available

Solvent separation test:

No data available

No data available

No data available

No data available

9.2. Other information

Solid content: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

Toxicological data are not available.

Acute toxicity

Toxicological data are not available.

Irritation and corrosivity

Irritating to eyes. Vapours may cause drowsiness and dizziness.

Sensitising effects

No data available

Severe effects after repeated or prolonged exposure

No data available

Carcinogenic/mutagenic/toxic effects for reproduction

Due to missing data no statement can be made whether the substance fullfills the criteria of CMR categories 1 or 2. Practical experiences do not give any evidence for CMR activity of categories 1 or 2.

Specific effects in experiment on an animal

No data available

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Practical experience

Observations relevant to classification

No data available



according to Regulation (EC) No 1907/2006

2-Propanol (Isopropyl alcohol/IPA), 250 ml

Print date: 15.04.2015 Product code: 9991813 Page 6 of 8

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160506

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals

Classified as hazardous waste.

Waste disposal number of used product

160506

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



according to Regulation (EC) No 1907/2006

2-Propanol (Isopropyl alcohol/IPA), 250 ml						
Print date: 15.04.2015	Product code: 9991813	Page 7 of 8				
Classification code:	F1					

Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

E₂

Inland waterways transport (ADN)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Special Provisions:601Limited quantity:1 L

Other applicable information (inland waterways transport)

F2

Marine transport (IMDG)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:-Limited quantity:1 LEmS:F-E, S-D

Other applicable information (marine transport)

F2

Air transport (ICAO)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A180Limited quantity Passenger:1 L

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2 : Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no



according to Regulation (EC) No 1907/2006

2-Propanol (Isopropyl alcohol/IPA), 250 ml

Print date: 15.04.2015 Product code: 9991813 Page 8 of 8

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Water contaminating class (D): 3 - highly water contaminating

SECTION 16: Other information

Relevant R-phrases (Number and full text)

Highly flammable.Irritating to eyes.

Vapours may cause drowsiness and dizziness.

Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.